

Technical sheet

BLACKBURN occupational boots



Product code: 6580-O2



| | |
|---------------------|-------------------------------------------------------------------------------------|
| upper | dry mild cowhide leather in a thickness of 1,9 - 2,1 mm |
| lining | breathable thermo-insulation MEMBRANE FREE-TEX® |
| inner insole | expanded polyurethane of high absorbency, antistatic |
| outsole | EVA/RUBBER - antistatic, glued construction |
| size | 36 - 48 |
| standard | EN ISO 20347:2012 |
| version | O2 WR CI SRA - without composite toe cap and kevlar midsole, hydrophobic, FREE-TEX® |

Properties

| | |
|-----------------------------------------------------------|------------|
| PL Midsole penetration protection nonmetallic - PL | No |
| PS Midsole penetration protection nonmetallic - PS | No |
| SR Antislip prop. on ceramic with glycerol | No |
| WPA Water resistant upper | No |
| HRO Resist. of the outsole against contact heat | No |
| WR Water resistant | Yes |
| WRU Water resistant upper | Yes |
| CI Insulation against cold | Yes |
| HI Insulation of the outsole against heat | No |
| FO Resist. of the outsole against fuel oils | No |
| P Midsole penetration protection | No |
| E Energy absorption in the heel area | No |
| M Instep protection | No |
| A Antistatic properties | No |
| AN Ankle protection | No |
| CR Cut resistant upper | No |
| SRA Antislip prop. on ceramic tile with SLS | Yes |
| SRB Antislip prop. on smooth steel with glycerol | No |
| SRC Antislip resistance SRA + SRB | No |
| Free-tex Membrane | Yes |
| Michelin Michelin® sole | No |
| BOA BOA Fit System | No |
| NON-METALIC Footwear without metal parts | No |
| ESD antistatic properties ESD | No |
| Winter Winter footwear | No |
| ANTICUT Anti-cut boots | No |
| Standard | 20347:2012 |
| Shoe marking | O2 |

Logistics parameters

| Velikost | Net weight | Gross weight | Sales box - width | Sales box - length | Sales box - height | Group packaging - width | Group packaging - length | Group packaging - height | Group packaging - weight | Vnitřní délka obuvi |
|----------|------------|--------------|-------------------|--------------------|--------------------|-------------------------|--------------------------|--------------------------|--------------------------|---------------------|
| 36 | 1,13 kg | 1,46 kg | 305 mm | 330 mm | 120 mm | 620 mm | 635 mm | 350 mm | 15,80 kg | 0,0 mm |
| 37 | 1,17 kg | 1,50 kg | 305 mm | 330 mm | 120 mm | 620 mm | 635 mm | 350 mm | 16,20 kg | 0,0 mm |
| 38 | 1,18 kg | 1,53 kg | 305 mm | 330 mm | 120 mm | 620 mm | 635 mm | 350 mm | 16,40 kg | 0,0 mm |
| 39 | 1,24 kg | 1,28 kg | 305 mm | 330 mm | 120 mm | 620 mm | 640 mm | 350 mm | 17,20 kg | 0,0 mm |
| 40 | 1,31 kg | 1,65 kg | 305 mm | 330 mm | 120 mm | 620 mm | 640 mm | 350 mm | 17,80 kg | 0,0 mm |
| 41 | 1,36 kg | 1,71 kg | 305 mm | 330 mm | 120 mm | 620 mm | 640 mm | 350 mm | 18,20 kg | 0,0 mm |
| 42 | 1,39 kg | 1,73 kg | 305 mm | 330 mm | 120 mm | 620 mm | 640 mm | 350 mm | 18,60 kg | 0,0 mm |
| 43 | 1,46 kg | 1,86 kg | 330 mm | 360 mm | 135 mm | 675 mm | 700 mm | 390 mm | 20,20 kg | 0,0 mm |
| 44 | 1,47 kg | 1,87 kg | 330 mm | 360 mm | 135 mm | 675 mm | 700 mm | 390 mm | 20,60 kg | 0,0 mm |
| 45 | 1,55 kg | 1,95 kg | 330 mm | 360 mm | 135 mm | 675 mm | 700 mm | 390 mm | 21,20 kg | 0,0 mm |
| 46 | 1,59 kg | 1,99 kg | 330 mm | 360 mm | 135 mm | 675 mm | 700 mm | 390 mm | 21,80 kg | 0,0 mm |
| 47 | 1,68 kg | 2,09 kg | 330 mm | 360 mm | 135 mm | 675 mm | 700 mm | 390 mm | 22,20 kg | 0,0 mm |

Business parameters

| | |
|----------------|----------|
| Tarric | 64039113 |
| Country | CN |

Weight 1,50 kg
Add Unit NPR
Add Quantity 1