

# Technical sheet

## MADISON low cut safety shoes



Product code: 2595-S1



<b>upper</b>	dry mild cowhide leather NUBUCK in a thickness of 1,8 - 2,0 mm
<b>lining</b>	laminated breathable fabric MESH
<b>inner insole</b>	HI-POLY - padded, anatomically shaped, made of porous polyurethane foam, coated with fabric MESH, antistatic
<b>outsole</b>	PU/PU - resistant to fuel oils, antistatic, antislip, double density injection
<b>size</b>	39 - 47
<b>standard</b>	EN ISO 20345:2011
<b>version</b>	S1 FO SRA - with steel toe cap

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	No
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	No
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	No
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	Yes
<b>P</b> Midsole penetration protection	No
<b>E</b> Energy absorption in the heel area	Yes
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	Yes
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	Yes
<b>SRB</b> Antislip prop. on smooth steel with glycerol	No
<b>SRC</b> Antislip resistance SRA + SRB	No
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	No
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No
<b>Standard</b>	20345:2012
<b>Shoe marking</b>	S1

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
39	0,98 kg	1,32 kg	220 mm	325 mm	125 mm	470 mm	630 mm	335 mm	14,80 kg	0,0 mm
40	1,03 kg	1,38 kg	220 mm	325 mm	125 mm	470 mm	630 mm	335 mm	15,20 kg	0,0 mm
41	1,09 kg	1,45 kg	220 mm	325 mm	125 mm	470 mm	630 mm	335 mm	15,80 kg	0,0 mm
42	1,15 kg	1,51 kg	220 mm	325 mm	125 mm	470 mm	630 mm	335 mm	16,20 kg	0,0 mm
43	1,16 kg	1,55 kg	230 mm	345 mm	125 mm	480 mm	650 mm	365 mm	17,00 kg	0,0 mm
44	1,21 kg	1,60 kg	230 mm	345 mm	125 mm	480 mm	650 mm	365 mm	17,60 kg	0,0 mm
45	1,27 kg	1,69 kg	230 mm	345 mm	125 mm	480 mm	650 mm	365 mm	18,20 kg	0,0 mm
46	1,27 kg	1,69 kg	230 mm	345 mm	125 mm	480 mm	650 mm	365 mm	18,60 kg	0,0 mm
47	1,31 kg	1,69 kg	230 mm	345 mm	125 mm	480 mm	650 mm	365 mm	18,80 kg	0,0 mm

## Business parameters

<b>Tarric</b>	64034000
<b>Country</b>	CN
<b>Weight</b>	1,40 kg
<b>Add Unit</b>	NPR
<b>Add Quantity</b>	1