

Technical sheet

WIENNA low cut safety shoes



Product code: 2885-S1



| | |
|---------------------|---|
| upper | cowhide leather with pattern in a thickness of 1,8 - 2,0 mm |
| lining | laminated breathable fabric MESH |
| inner insole | HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic |
| outsole | PU/PU - resistant to fuel oils, antistatic, antislip, double density injection |
| size | 36 - 48 |
| standard | EN ISO 20345:2011 |
| version | S1 SRC - with steel toe cap |

Properties

| | |
|---|------------|
| PL Midsole penetration protection nonmetallic - PL | No |
| PS Midsole penetration protection nonmetallic - PS | No |
| SR Antislip prop. on ceramic with glycerol | No |
| WPA Water resistant upper | No |
| HRO Resist. of the outsole against contact heat | No |
| WR Water resistant | No |
| WRU Water resistant upper | No |
| CI Insulation against cold | No |
| HI Insulation of the outsole against heat | No |
| FO Resist. of the outsole against fuel oils | Yes |
| P Midsole penetration protection | No |
| E Energy absorption in the heel area | Yes |
| M Instep protection | No |
| A Antistatic properties | Yes |
| AN Ankle protection | No |
| CR Cut resistant upper | No |
| SRA Antislip prop. on ceramic tile with SLS | Yes |
| SRB Antislip prop. on smooth steel with glycerol | Yes |
| SRC Antislip resistance SRA + SRB | Yes |
| Free-tex Membrane | No |
| Michelin Michelin® sole | No |
| BOA BOA Fit System | No |
| NON-METALIC Footwear without metal parts | No |
| ESD antistatic properties ESD | No |
| Winter Winter footwear | No |
| ANTICUT Anti-cut boots | No |
| Standard | 20345:2012 |
| Shoe marking | S1 |

Logistics parameters

| Velikost | Net weight | Gross weight | Sales box - width | Sales box - length | Sales box - height | Group packaging - width | Group packaging - length | Group packaging - height | Group packaging - weight | Vnitřní délka obuvi |
|----------|------------|--------------|-------------------|--------------------|--------------------|-------------------------|--------------------------|--------------------------|--------------------------|---------------------|
| 36 | 0,99 kg | 1,18 kg | 200 mm | 315 mm | 115 mm | 425 mm | 600 mm | 345 mm | 12,60 kg | 239,0 mm |
| 37 | 0,95 kg | 1,14 kg | 200 mm | 315 mm | 115 mm | 425 mm | 600 mm | 345 mm | 12,20 kg | 245,7 mm |
| 38 | 1,00 kg | 1,20 kg | 200 mm | 315 mm | 115 mm | 425 mm | 600 mm | 345 mm | 12,80 kg | 252,3 mm |
| 39 | 1,01 kg | 1,20 kg | 200 mm | 315 mm | 115 mm | 425 mm | 600 mm | 345 mm | 12,80 kg | 259,0 mm |
| 40 | 1,05 kg | 1,25 kg | 200 mm | 315 mm | 115 mm | 425 mm | 600 mm | 345 mm | 13,40 kg | 265,7 mm |
| 41 | 1,10 kg | 1,30 kg | 200 mm | 315 mm | 115 mm | 425 mm | 600 mm | 345 mm | 13,60 kg | 272,3 mm |
| 42 | 1,13 kg | 1,33 kg | 200 mm | 315 mm | 115 mm | 425 mm | 600 mm | 345 mm | 14,00 kg | 279,0 mm |
| 43 | 1,23 kg | 1,42 kg | 205 mm | 330 mm | 120 mm | 430 mm | 630 mm | 355 mm | 15,00 kg | 285,7 mm |
| 44 | 1,24 kg | 1,46 kg | 205 mm | 330 mm | 120 mm | 430 mm | 630 mm | 355 mm | 15,40 kg | 292,3 mm |
| 45 | 1,29 kg | 1,51 kg | 210 mm | 350 mm | 125 mm | 440 mm | 650 mm | 375 mm | 16,00 kg | 299,0 mm |
| 46 | 1,30 kg | 1,54 kg | 210 mm | 350 mm | 125 mm | 440 mm | 650 mm | 375 mm | 16,20 kg | 305,7 mm |
| 47 | 1,35 kg | 1,58 kg | 210 mm | 350 mm | 125 mm | 440 mm | 650 mm | 375 mm | 16,60 kg | 312,4 mm |
| 48 | 1,37 kg | 1,59 kg | 210 mm | 350 mm | 125 mm | 440 mm | 650 mm | 375 mm | 16,90 kg | 319,0 mm |

Business parameters

| | |
|----------------|----------|
| Tarric | 64034000 |
| Country | CN |

| | |
|---------------------|---------|
| Weight | 1,32 kg |
| Add Unit | NPR |
| Add Quantity | 1 |