

# Technical sheet

## SANMARINO ankle occupational shoes, winter design

Product code: 3170-01W



|                     |  |
|---------------------|--|
| <b>upper</b>        | brushed cow suede leather VELOUR in a thickness of 1,6 - 1,8 mm                |
| <b>lining</b>       | hair plush DELTA   |
| <b>inner insole</b> | anatomically shaped with latex heel pad, coated with textile MESH, antistatic  |
| <b>outsole</b>      | PU/PU - resistant to fuel oils, antistatic, antislip, double density injection |
| <b>size</b>         | 36 - 50  |
| <b>standard</b>     | EN ISO 20347:2012  |
| <b>version</b>      | O1 FO SRA - without steel toe cap, winter design                               |

## Properties

|   |            |
|---|------------|
| <b>PL</b> Midsole penetration protection nonmetallic - PL | No         |
| <b>PS</b> Midsole penetration protection nonmetallic - PS | No         |
| <b>SR</b> Antislip prop. on ceramic with glycerol         | No         |
| <b>WPA</b> Water resistant upper                          | No         |
| <b>HRO</b> Resist. of the outsole against contact heat    | No         |
| <b>WR</b> Water resistant                                 | No         |
| <b>WRU</b> Water resistant upper                          | No         |
| <b>CI</b> Insulation against cold                         | No         |
| <b>HI</b> Insulation of the outsole against heat          | No         |
| <b>FO</b> Resist. of the outsole against fuel oils        | Yes        |
| <b>P</b> Midsole penetration protection                   | No         |
| <b>E</b> Energy absorption in the heel area               | Yes        |
| <b>M</b> Instep protection                                | No         |
| <b>A</b> Antistatic properties                            | Yes        |
| <b>AN</b> Ankle protection                                | No         |
| <b>CR</b> Cut resistant upper                             | No         |
| <b>SRA</b> Antislip prop. on ceramic tile with SLS        | Yes        |
| <b>SRB</b> Antislip prop. on smooth steel with glycerol   | No         |
| <b>SRC</b> Antislip resistance SRA + SRB                  | No         |
| <b>Free-tex</b> Membrane                                  | No         |
| <b>Michelin</b> Michelin® sole                            | No         |
| <b>BOA</b> BOA Fit System                                 | No         |
| <b>NON-METALIC</b> Footwear without metal parts           | No         |
| <b>ESD</b> antistatic properties ESD                      | No         |
| <b>Winter</b> Winter footwear                             | Yes        |
| <b>ANTICUT</b> Anti-cut boots                             | No         |
| <b>Standard</b>   | 20347:2012 |
| <b>Shoe marking</b>                                       | O1         |

## Logistics parameters

| Velikost | Net weight | Gross weight | Sales box - width | Sales box - length | Sales box - height | Group packaging - width | Group packaging - length | Group packaging - height | Group packaging - weight | Vnitřní délka obuvi |
|----------|------------|--------------|-------------------|--------------------|--------------------|-------------------------|--------------------------|--------------------------|--------------------------|---------------------|
| 36       | 0,96 kg    | 1,29 kg      | 240 mm            | 315 mm             | 120 mm             | 500 mm                  | 630 mm                   | 335 mm                   | 13,60 kg                 | 239,0 mm            |
| 37       | 0,97 kg    | 1,30 kg      | 240 mm            | 315 mm             | 120 mm             | 500 mm                  | 630 mm                   | 335 mm                   | 13,80 kg                 | 245,7 mm            |
| 38       | 1,00 kg    | 1,33 kg      | 240 mm            | 315 mm             | 120 mm             | 500 mm                  | 630 mm                   | 335 mm                   | 14,20 kg                 | 252,3 mm            |
| 39       | 1,07 kg    | 1,39 kg      | 240 mm            | 315 mm             | 120 mm             | 500 mm                  | 630 mm                   | 335 mm                   | 14,80 kg                 | 259,0 mm            |
| 40       | 1,08 kg    | 1,41 kg      | 240 mm            | 315 mm             | 120 mm             | 500 mm                  | 630 mm                   | 335 mm                   | 15,20 kg                 | 265,7 mm            |
| 41       | 1,13 kg    | 1,46 kg      | 240 mm            | 315 mm             | 120 mm             | 500 mm                  | 630 mm                   | 335 mm                   | 15,60 kg                 | 272,3 mm            |
| 42       | 1,17 kg    | 1,50 kg      | 240 mm            | 315 mm             | 120 mm             | 500 mm                  | 630 mm                   | 335 mm                   | 15,80 kg                 | 279,0 mm            |
| 43       | 1,20 kg    | 1,59 kg      | 260 mm            | 360 mm             | 125 mm             | 530 mm                  | 660 mm                   | 380 mm                   | 17,00 kg                 | 285,7 mm            |
| 44       | 1,25 kg    | 1,62 kg      | 260 mm            | 360 mm             | 125 mm             | 530 mm                  | 660 mm                   | 380 mm                   | 17,40 kg                 | 292,3 mm            |
| 45       | 1,27 kg    | 1,65 kg      | 260 mm            | 360 mm             | 125 mm             | 530 mm                  | 660 mm                   | 380 mm                   | 17,60 kg                 | 299,0 mm            |
| 46       | 1,33 kg    | 1,71 kg      | 260 mm            | 360 mm             | 125 mm             | 530 mm                  | 660 mm                   | 380 mm                   | 18,20 kg                 | 305,7 mm            |
| 47       | 1,38 kg    | 1,76 kg      | 260 mm            | 360 mm             | 125 mm             | 530 mm                  | 660 mm                   | 380 mm                   | 18,60 kg                 | 312,4 mm            |
| 48       | 1,42 kg    | 1,80 kg      | 260 mm            | 360 mm             | 125 mm             | 530 mm                  | 660 mm                   | 380 mm                   | 19,00 kg                 | 319,0 mm            |

## Business parameters

|                |          |
|----------------|----------|
| <b>Tarric</b>  | 64039113 |
| <b>Country</b> | CN       |

|                     |         |
|---------------------|---------|
| <b>Weight</b>       | 1,45 kg |
| <b>Add Unit</b>     | NPR     |
| <b>Add Quantity</b> | 1       |