

Technical sheet

TOKIO low cut safety shoes

Product code: 2125-S1ESD



| | |
|---------------------|---|
| upper | brushed cow suede leather VELOUR in a thickness of 1,6 - 1,8 mm |
| lining | laminated breathable fabric MESH |
| inner insole | HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic |
| outsole | PU/PU - resistant to fuel oils, antistatic, antislip, double density injection |
| size | 36 - 48 |
| standard | EN ISO 20345:2011, EN ISO 61340-5-1:2016 |
| version | S1 ESD SRA - with plastic toe cap - antistatic properties ESD |

Properties

| | |
|---|------------|
| PL Midsole penetration protection nonmetallic - PL | No |
| PS Midsole penetration protection nonmetallic - PS | No |
| SR Antislip prop. on ceramic with glycerol | No |
| WPA Water resistant upper | No |
| HRO Resist. of the outsole against contact heat | No |
| WR Water resistant | No |
| WRU Water resistant upper | No |
| CI Insulation against cold | No |
| HI Insulation of the outsole against heat | No |
| FO Resist. of the outsole against fuel oils | Yes |
| P Midsole penetration protection | No |
| E Energy absorption in the heel area | Yes |
| M Instep protection | No |
| A Antistatic properties | Yes |
| AN Ankle protection | No |
| CR Cut resistant upper | No |
| SRA Antislip prop. on ceramic tile with SLS | Yes |
| SRB Antislip prop. on smooth steel with glycerol | No |
| SRC Antislip resistance SRA + SRB | No |
| Free-tex Membrane | No |
| Michelin Michelin® sole | No |
| BOA BOA Fit System | No |
| NON-METALIC Footwear without metal parts | No |
| ESD antistatic properties ESD | Yes |
| Winter Winter footwear | No |
| ANTICUT Anti-cut boots | No |
| Standard | 20345:2012 |
| Shoe marking | S1 |

Logistics parameters

| Velikost | Net weight | Gross weight | Sales box - width | Sales box - length | Sales box - height | Group packaging - width | Group packaging - length | Group packaging - height | Group packaging - weight | Vnitřní délka obuvi |
|----------|------------|--------------|-------------------|--------------------|--------------------|-------------------------|--------------------------|--------------------------|--------------------------|---------------------|
| 36 | 0,79 kg | 1,04 kg | 200 mm | 315 mm | 115 mm | 420 mm | 600 mm | 340 mm | 11,20 kg | 231,0 mm |
| 37 | 0,82 kg | 1,07 kg | 200 mm | 315 mm | 115 mm | 420 mm | 600 mm | 340 mm | 11,40 kg | 237,7 mm |
| 38 | 0,82 kg | 1,07 kg | 200 mm | 315 mm | 115 mm | 420 mm | 600 mm | 340 mm | 11,60 kg | 244,3 mm |
| 39 | 0,87 kg | 1,12 kg | 200 mm | 315 mm | 115 mm | 420 mm | 600 mm | 340 mm | 12,00 kg | 251,0 mm |
| 40 | 0,88 kg | 1,12 kg | 200 mm | 315 mm | 115 mm | 420 mm | 600 mm | 340 mm | 12,20 kg | 257,7 mm |
| 41 | 0,92 kg | 1,17 kg | 200 mm | 315 mm | 115 mm | 420 mm | 600 mm | 340 mm | 12,40 kg | 264,3 mm |
| 42 | 0,96 kg | 1,21 kg | 200 mm | 315 mm | 115 mm | 420 mm | 600 mm | 340 mm | 12,80 kg | 271,0 mm |
| 43 | 1,01 kg | 1,26 kg | 205 mm | 330 mm | 125 mm | 430 mm | 620 mm | 360 mm | 13,40 kg | 277,7 mm |
| 44 | 1,04 kg | 1,29 kg | 205 mm | 330 mm | 125 mm | 430 mm | 620 mm | 360 mm | 13,60 kg | 284,3 mm |
| 45 | 1,08 kg | 1,33 kg | 205 mm | 330 mm | 125 mm | 430 mm | 620 mm | 360 mm | 14,00 kg | 291,0 mm |
| 46 | 1,10 kg | 1,38 kg | 210 mm | 350 mm | 130 mm | 440 mm | 655 mm | 375 mm | 14,60 kg | 299,7 mm |
| 47 | 1,12 kg | 1,40 kg | 210 mm | 350 mm | 130 mm | 440 mm | 655 mm | 375 mm | 15,00 kg | 304,4 mm |
| 48 | 1,51 kg | 1,43 kg | 210 mm | 350 mm | 130 mm | 440 mm | 655 mm | 375 mm | 15,30 kg | 311,0 mm |

Business parameters

| | |
|----------------|----------|
| Tarric | 64034000 |
| Country | CN |

| | |
|---------------------|---------|
| Weight | 1,27 kg |
| Add Unit | NPR |
| Add Quantity | 1 |