

Technical sheet

QUITO ankle safety shoes

Product code: 2490-S1



| | |
|---------------------|---|
| upper | cowhide leather in a thickness of 2,0 - 2,2 mm |
| lining | laminated breathable fabric MESH |
| inner insole | HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic |
| outsole | PU/RUBBER - up to 300°C, resistant to fuel oils, antistatic, antislip, double density injection |
| size | 39 - 48 |
| standard | EN ISO 20345:2022 |
| version | S1 FO HRO SR - with steel toe cap |

Properties

| | |
|---|------------|
| PL Midsole penetration protection nonmetallic - PL | No |
| PS Midsole penetration protection nonmetallic - PS | No |
| SR Antislip prop. on ceramic with glycerol | Yes |
| WPA Water resistant upper | No |
| HRO Resist. of the outsole against contact heat | Yes |
| WR Water resistant | No |
| WRU Water resistant upper | No |
| CI Insulation against cold | No |
| HI Insulation of the outsole against heat | No |
| FO Resist. of the outsole against fuel oils | Yes |
| P Midsole penetration protection | No |
| E Energy absorption in the heel area | Yes |
| M Instep protection | No |
| A Antistatic properties | Yes |
| AN Ankle protection | No |
| CR Cut resistant upper | No |
| SRA Antislip prop. on ceramic tile with SLS | No |
| SRB Antislip prop. on smooth steel with glycerol | No |
| SRC Antislip resistance SRA + SRB | No |
| Free-tex Membrane | No |
| Michelin Michelin® sole | No |
| BOA BOA Fit System | No |
| NON-METALIC Footwear without metal parts | No |
| ESD antistatic properties ESD | No |
| Winter Winter footwear | No |
| ANTICUT Anti-cut boots | No |
| Standard | 20345:2023 |
| Shoe marking | S1 |

Logistics parameters

| Velikost | Net weight | Gross weight | Sales box - width | Sales box - length | Sales box - height | Group packaging - width | Group packaging - length | Group packaging - height | Group packaging - weight | Vnitřní délka obuvi |
|----------|------------|--------------|-------------------|--------------------|--------------------|-------------------------|--------------------------|--------------------------|--------------------------|---------------------|
| 39 | 1,26 kg | 1,57 kg | 260 mm | 320 mm | 120 mm | 545 mm | 600 mm | 345 mm | 17,20 kg | 252,0 mm |
| 40 | 1,26 kg | 1,58 kg | 260 mm | 320 mm | 120 mm | 545 mm | 600 mm | 345 mm | 17,40 kg | 259,5 mm |
| 41 | 1,29 kg | 1,61 kg | 260 mm | 320 mm | 120 mm | 545 mm | 600 mm | 345 mm | 17,60 kg | 267,0 mm |
| 42 | 1,36 kg | 1,67 kg | 260 mm | 320 mm | 120 mm | 545 mm | 600 mm | 345 mm | 18,00 kg | 274,5 mm |
| 43 | 1,43 kg | 1,80 kg | 275 mm | 350 mm | 125 mm | 575 mm | 650 mm | 375 mm | 19,40 kg | 282,0 mm |
| 44 | 1,46 kg | 1,84 kg | 275 mm | 350 mm | 125 mm | 575 mm | 650 mm | 375 mm | 19,80 kg | 289,5 mm |
| 45 | 1,51 kg | 1,88 kg | 275 mm | 350 mm | 125 mm | 575 mm | 650 mm | 375 mm | 20,20 kg | 297,0 mm |
| 46 | 1,60 kg | 1,97 kg | 275 mm | 350 mm | 125 mm | 575 mm | 650 mm | 375 mm | 21,20 kg | 304,5 mm |
| 47 | 1,65 kg | 2,02 kg | 275 mm | 350 mm | 125 mm | 575 mm | 650 mm | 375 mm | 21,80 kg | 312,0 mm |
| 48 | 1,73 kg | 2,10 kg | 275 mm | 350 mm | 125 mm | 575 mm | 650 mm | 375 mm | 22,40 kg | 319,5 mm |

Business parameters

| | |
|-----------------|----------|
| Tarric | 64034000 |
| Country | CN |
| Weight | 1,67 kg |
| Add Unit | NPR |

Add Quantity 1