

# Technical sheet

## CORSICA low cut occupational shoes

Product code: 2055-O1ESD



<b>upper</b>	brushed cow suede leather VELOUR, coated in a thickness of 1,6 - 1,8 mm
<b>lining</b>	laminated breathable fabric MESH
<b>inner insole</b>	HI-POLY - anatomically shaped lightweight polyurethane foam coated with fabric MESH, antistatic
<b>outsole</b>	PU/PU - antistatic, antislip, double density injection
<b>size</b>	36 - 49
<b>standard</b>	EN ISO 20347:2022, EN ISO 61340-5-1:2016
<b>version</b>	O1 ESD SR - without composite toe cap and kevlar midsole - antistatic properties ESD, NON METALIC, blue color

## Properties

<b>PL</b> Midsole penetration protection nonmetallic - PL	No
<b>PS</b> Midsole penetration protection nonmetallic - PS	No
<b>SR</b> Antislip prop. on ceramic with glycerol	Yes
<b>WPA</b> Water resistant upper	No
<b>HRO</b> Resist. of the outsole against contact heat	No
<b>WR</b> Water resistant	No
<b>WRU</b> Water resistant upper	No
<b>CI</b> Insulation against cold	No
<b>HI</b> Insulation of the outsole against heat	No
<b>FO</b> Resist. of the outsole against fuel oils	No
<b>P</b> Midsole penetration protection	No
<b>E</b> Energy absorption in the heel area	Yes
<b>M</b> Instep protection	No
<b>A</b> Antistatic properties	Yes
<b>AN</b> Ankle protection	No
<b>CR</b> Cut resistant upper	No
<b>SRA</b> Antislip prop. on ceramic tile with SLS	No
<b>SRB</b> Antislip prop. on smooth steel with glycerol	No
<b>SRC</b> Antislip resistance SRA + SRB	No
<b>Free-tex</b> Membrane	No
<b>Michelin</b> Michelin® sole	No
<b>BOA</b> BOA Fit System	No
<b>NON-METALIC</b> Footwear without metal parts	No
<b>ESD</b> antistatic properties ESD	Yes
<b>Winter</b> Winter footwear	No
<b>ANTICUT</b> Anti-cut boots	No
<b>Standard</b>	20347:2022
<b>Shoe marking</b>	O1

## Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
36	0,71 kg	0,97 kg	200 mm	320 mm	115 mm	420 mm	600 mm	330 mm	10,40 kg	237,7 mm
37	0,75 kg	1,00 kg	200 mm	320 mm	115 mm	420 mm	600 mm	330 mm	10,60 kg	244,3 mm
38	0,77 kg	1,03 kg	200 mm	320 mm	115 mm	420 mm	600 mm	330 mm	11,00 kg	251,0 mm
39	0,79 kg	1,05 kg	200 mm	320 mm	115 mm	420 mm	600 mm	330 mm	11,20 kg	257,7 mm
40	0,82 kg	1,08 kg	200 mm	320 mm	115 mm	420 mm	600 mm	330 mm	11,40 kg	264,3 mm
41	0,85 kg	1,10 kg	200 mm	320 mm	115 mm	420 mm	600 mm	330 mm	11,60 kg	271,0 mm
42	0,88 kg	1,13 kg	200 mm	320 mm	115 mm	420 mm	600 mm	330 mm	12,00 kg	277,7 mm
43	0,89 kg	1,17 kg	200 mm	330 mm	120 mm	430 mm	620 mm	345 mm	12,40 kg	284,3 mm
44	0,95 kg	1,23 kg	200 mm	330 mm	120 mm	430 mm	620 mm	345 mm	13,00 kg	291,0 mm
45	0,98 kg	1,25 kg	200 mm	330 mm	120 mm	430 mm	620 mm	345 mm	13,40 kg	297,7 mm
46	1,05 kg	1,32 kg	210 mm	345 mm	125 mm	440 mm	650 mm	370 mm	14,00 kg	304,4 mm
47	1,07 kg	1,35 kg	210 mm	345 mm	125 mm	440 mm	650 mm	370 mm	14,20 kg	311,0 mm
48	1,09 kg	1,37 kg	210 mm	345 mm	125 mm	440 mm	650 mm	370 mm	14,40 kg	317,7 mm
49	1,12 kg	1,42 kg	210 mm	345 mm	125 mm	440 mm	650 mm	370 mm	15,00 kg	0,0 mm

## Business parameters

**Tarric** 64039993

<b>Country</b>	CN
<b>Weight</b>	1,15 kg
<b>Add Unit</b>	NPR
<b>Add Quantity</b>	1